Data Sheet

SCENICVIEW E19-6
19 Inch LCD Display

An attractive price doesn't mean that you have to compromise on style or performance. Sleek and space-saving, the SCENICVIEW E19-6 is the best choice LCD. It offers best performance for the office and multimedia applications. It is the ideal LCD for those seeking to upgrade their bulky CRT with limited budget.

Highlights

- Best performance to an affordable price
  - Office applications
  - Internet and multimedia are supported best
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent color purity
- Well balanced brightness uniformity
- Excellent high contrast   800:1
- Space saving design

Technical highlights

- 19" (48cm) LCD Display
- Excellent contrast   800:1
- Brightness   300 cd/m^2
- Fast response time (typ.)   5ms

Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability

Visible screen diagonal	19 inch (48 cm)
Resolution	
Pixels	1280 x 1024
Pixels*	1024 x 768
Pixels*	800 x 600
* expanded	
Picture size	376.3 x 301 mm
Colors	16.2 million
Pixel Pitch	0.294 mm
Frequencies	
Horizontal	31 - 81 kHz
Vertical	56 - 75 Hz
Brightness (typical)	300 cd/m²
Contrast (typical)	800:1
Viewing angle (typical)	
Horizontal	160°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	
Brightness (Back light)	
Contrast, Volume control	
Picture position (horizontal and vertical)	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
OSD Language	
English, German, French, Italian, Spanish, Polish, Dutch, Russian	
Base	
Tilt angle	-5° / +20°
Video input	1 x D-SUB, 1 x DVI
Audio input / output	
Audio signal input	3.5 mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

Electrical values (internal power supply)	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	< 50 W
Stand by	< 1 W
Protection class	1
Temperatures/ dimensions/ weight	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	375 x 410 x 214 mm
(with Stand)	
Weight (Monitor only):	4.5 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
Compliance with standards	
Product safety	EN60950, NEMKO
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024, EN61000-3-2/-3);TCO 03
Accessories	
Power cable (1.8 m)*	For wall socket Euro-Schuko-Type CEE7
Plug type on Monitor	IEC-320-C13
Data cable (1.8 m)*	D-SUB (15-pin)
Audio Cable (1.8m)*	3.5 mm stereo phone jack
* detachable on display	
Special features	Standardized mounting interface (according VESA FPMPMI 100 mm) Integrated audio Kensington Lock
Order code	S26361-K1199-V376
EAN	4333643067137